APPENDIX

VOYAGE DATA RECORDER PERFORMANCE TEST REPORT

(Note: Insert Yes for success, No for failure or N/A for non-fitted interfaces in these boxes, as appropriate)

Ship's details

Ship's name	
Flag	
IMO number	
Date keel laid	
Gross tonnage	

Voyage data recorder details

Manufacturer	
Model	
System serial number	
Software version number	
Date fitted	

Inspection details

Name of person conducting testing	
Company	
Inspection date	
Inspection location	

1 Pre-existing alarms

Confirm that no alarms were present at start of procedure			
2 Power supply alarm check			
Remove source of external power. Confirm that alarm is activated.			
Record time (hh.mm)		 	

3 Reserve power source check

Allow VDR to continue run	ning for 1 hour 55 minutes from '2' above.	 	
Confirm that equipment is	still operating at this time, with no additional alarms.		
Record time (hh.mm)			
4 Reserve power s	ource shutdown check		
2 hours 05 minutes from stopped recording.	'2' above confirm that the VDR has automatically		
Record time (hh.mm)			
5 Battery expiry da	ites		
Battery	Expiry date (where applicable)	 	
Acoustic beacon			
Reserve power source			
6 Acoustic beacon	test		
Using manufacturer's test			

7 Overall condition of equipment

	n or equipment				
Inspect equipment and re-	cord condition, tick if satisfa	actory:			
Sub unit	Notes on condition				
Protective capsule					
External cables					
Main unit					
8 Interfaces: Oper	ation and recording				
Date and time	Preferably external to				
	ship (e.g. Global				
	Navigation Satellite				
	System.)				
Ship's position	Electronic Positioning				
	system				
Speed (through water or	Ship's designated				
over ground)	speed and distance				
	measuring equipment				
Heading	Ship's compass				
Bridge audio	1 or more bridge				
	microphones				
Communications Audio	VHF				
.					
Radar data- post display	Master radar display				
selection	(both radars, where				
ECDIS	applicable) ECDIS display in use,				
ECDIS	where fitted				
AIS	All AIS data				
AIS	All AIS data				
Rolling motion	Electronic inclinometer,				
	where fitted				
Configuration data	Where applicable				
g					
Electronic logbook	Where fitted				
5					
Water depth	Echo sounder				
Main alarms	All mandatory alarms on				
	bridge				
Rudder order and	Steering gear and				
response	autopilot			·	
Engine order and	Telegraphs, controls				
response	and thrusters				
Hull openings status	All mandatory status				
	information displayed				
Motorialt and fire deer	on bridge			[]	
Watertight and fire door	All mandatory status				
status	information displayed on bridge				
Acceleration and hull	Hull stress and				
	i iuii suless allu			1	

stresses

direction

Wind speed and

response monitoring

Anemometer where

fitted

equipment where fitted

9 Float-free capsule

For float-free capsules approved in accordance
with resolution MSC.333(90): an examination
according to MSC.1/Circ.1040/Rev.1 has been
conducted.

	 -

Yes No N/A

10 Change or repair of sensors

Check maintenance records of VDR			Í	
Confirm any defects properly rectified				
Person authorized by the Manufacturer Ship's representative				
Date	Date			

If the manufacturer does not complete a review and issue a completed test report within 45 days, this test report should go forward for certification.

11 Manufacturer's analysis

Note – This confirms the endorsement by the manufacturer of the tests and that the master record/database has been checked.

Manufacturer's analysis of 12-hour log is attached and in accordance with International Electrotechnical Commission (IEC) 61996 Maritime navigation and radiocommunication equipment and systems – Shipborne voyage data recorder (VDR) – Performance requirements – Methods of testing and required test results section 4.6 – Data items to be recorded (resolution A.861(20), section 5.4). Confirmation that all data is available throughout the 12-hour recording.

Date and time of above log.

12 Observations and additional manufacturer's requirements

Note – This specifically provides for the logging of significant events that may have occurred on board since the previous test, including the refitting of equipment or major unit change to existing equipment. – Any or all of which may have an impact on the availability or quality of the VDR/S-VDR input signal.

This performance test was conducted in accordance with SOLAS regulation V/18.8 and forms part of the procedure for the issue of the Annual Performance Test Certificate. The results, information and any comments should be relayed to the manufacturer in accordance with the instructions contained within

the Operation Manual. Subject to satisfactory results, an Annual Performance Test Certificate will then be issued.

In accordance with the principles of harmonization of Certificates, the Certificate, when issued, will remain valid until the next annual re-validation of that Certificate, subject to the equipment being maintained in appropriate operational condition.
